

Underhaug

UNDERHAUG 2200

The compact,
versatile and lightweight
2-row potato harvester

tkS

MEKANISKE

www.tksmek.com



Underhaug 2200

2-row potato harvester

After it's introduction in the late 80's the 2200 has been manufactured continuously for more than 20 years – is still in Underhaug's product range, and only minor changes and additions have been found to be necessary during this period.

The 2200 has been sold in hundreds and hundreds to satisfied customers on all continents of the world – to seed growers and commercial operators alike, and many 2200s are still being used after more than 20 years of service.

The verdict is that the 2200 is a unique machine; low weight, easy to handle, simple adjustments, long lasting – and reasonably priced for the job it does.

Underhaug 2200 harvester has definitely passed the test of time!

2200 weighs only approx. 3500 kgs. It can, therefore, be operated by smaller tractors with low fuel consumption. It pulls easily in all conditions, it offers a tight turn radius on head lands, and all hydraulic functions are easily operated via the electric control panel in the tractor cab. The digging unit floats independently from the main frame ensuring the correct digging depth set by plastic diabolos.



In addition to operate as a normal 2-row harvester, the 2200 can easily and with very small alterations be turned into an windrower, and with a minimum of field management crops from 2 or even 4 rows can be placed between the 2 rows that will be lifted in the traditional way later. This method has several advantages and has a favourable effect on crop quality.

Another unique feature is the Non-stop system which is optional. Instead of waiting for an empty trailer, the machine operator just reverses the elevator belt direction, and deposits the crop between the 2 rows to the left. This crop will in turn be lifted together with the rows on the next pass.

As an extra cleaning device – a flight elevator may be placed over the first digging web. By running this conveyor and it's gentle rubber flaps a little slower than the web itself, the flights will take out a lot of soil and clods. In addition it will help feed the machine when digging down hill, and will also prevent any roll back of potatoes on the web.

2200 can be supplied with or without a picking table. The picking table offers infinite web speed control, and adjustable platforms for the four operators.

A variety of web openings are available.

Technical specifications 2200:

Length incl drawbar and picking table	8,9m
Transport height	3,1m
Width	2,82m
Net weight	3650kgs
Axle load	3150kgs
Load on drawbar (with tyres 500/50-17")	500kgs
Row distance	from 75cms and up
Digging system	floating
3 shares per row or full width share	

Options:

Windrowing kit from 75 cms rows

Non-stop kit from 75cms rows

Picking table

Canopy for picking table

Flight conveyor over 1st web

Hydraulic lane adjustment

Fall damper from elevator

Road lights

Elevator control from tractor cab

For more information and price quotations please contact:



Torlandsveien 3, N-4365 Nærbø, Norway
Tel. +47 51 43 63 00, Fax +47 51 43 48 62
www.tksmek.com e-mail: post@tksmek.no

Importer:

Dealer: