

**Underhaug**

# UNDERHAUG 3744

4-row trailed potato planter with hydraulic hopper

**NEW**

**tk**s

**MEKANISKE**

[www.tksmek.com](http://www.tksmek.com)



# Underhaug 3744

## 4-row potato planters

TKS is proud to introduce its latest range of cup potato planters for the professional growers world-wide.

For decades Underhaug planters have been known for their accuracy, high performance and durability. They are highly appreciated among operators for their ease of operation, easy adjustments, simple design and low maintenance requirements. Compared to earlier models the Underhaug 3744 offers many new and unique features.

**Underhaug 3744 is a new, favourably priced trailed 4-row machine. Mechanically driven from a large ground wheel, and with a hopper that holds 3,5 tons of seed, this machine will be the new work horse among all the Underhaug models. The capacity of 3744 is sufficiently high to satisfy even the larger growing operations, and the flexibility of 4-row equipment makes the 3744 a very interesting alternative for the high volume grower.**

The machine straddles all 4 rows on its two large tyres. The adjustable front lifting cylinder controls planting depth (stepless), and together with the hydraulic raising system on the rear wheels, 3744 offers an excellent ground clearance when turning – and for transport..

Standard details on the 3744 include HD planting shares with shock absorbers, roller discs for covering the seed, automatic track markers, choice of 30 seed spacings, durable steel seed cups.



### Technical specifications 3744:

Length	4,92 m incl. draw bar
Width	3,45m (75cm row distance)
Height	1,55m – 2,76m
Weight	2,35 t (standard version)
Potato hopper capacity	3,5 – 4 t (depends on row distance)
Fertiliser tank capacity	1,8t
Landwheels (2 pcs)	11,2x28"
Drive wheel	7,5 x 16"
Standard planting shares	HD w/shock absorbers
Seed spacings	10 – 60 cms
Steel planting cups with 2 insert sizes (plastic)	
Automatic track markers	



As with all Underhaug planters, the main focus is on simplicity, accuracy, reliability, ease of operation and maintenance. In the 3744 machine all of these goals have been achieved, and these design features are highly appreciated both by owners and operators in the field.

Seed spacings are easily set in the gearbox (no tools required), left-over seed is quickly discharged from the planting units with the hinged bottom parts, belt agitation is simple and reliable, planting belts are quickly and easily tightened by handles on the top of the units, and also quickly slackened for storage. The very few moving parts in the 3744 are the best of guarantees for a very low need for spares. When spares are needed, all parts are easily accessible and easy to change. The Underhaug planting drive system will indeed surprise you with its simplicity!

The 3744 is equipped with the well-known Underhaug planting unit incorporating the large belt turning shaft at the top. This offers high planting speed (depending on seed spacing) without this interfering with the accuracy in spacing.

The large hopper capacity – both for seed and fertiliser – keeps the down time to a minimum, and the efficiency of 3744 correspondingly high.

### Options:

Electronic planting monitor  
Hydr. tram lining system  
Fertiliser machine  
Coulters for fertiliser placing  
Floating planting shares  
Ridge former

**The Underhaug 3700 range includes 2-, 4-, 6- and 8-row potato planters.**

For more information and price quotations please contact:

**tkS**

MEKANISKE

Torlandsveien 3, N-4365 Nærbø, Norway  
Tel. +47 51 43 63 00, Fax +47 51 43 48 62  
www.tksmek.com e-mail: post@tksmek.no

Importer:

Dealer: