

**Underhaug**

**UNDERHAUG 5660**

**1-row potato harvester**

**tkS**

**MEKANISKE**

[www.tksmek.com](http://www.tksmek.com)

**NEW**



# Underhaug 5660

## 1 row harvester

5660 is the latest Underhaug 1 - row trailed bunker machine. Hopper capacity of this harvester is 6 tons. As an option a separate 1 ton hopper for the small potatoes is available. Again a unique harvester, with incorporated flight conveyor over digging web. This ensures the gentlest transport of the crop, increases sieving capacity considerably, and eases the feeding of soil into the machine at all angles.

The haulm web is driven separately, and the speed is easily controlled from the picking table.

The angle of the two hedgehog belts is adjustable, and so is the position of the two deflector rollers. This, in combination with a double rotor deflector over the second hedgehog belt, offers an excellent sieving, cleaning and separation efficiency.

Automatic functions are available : Depth control, row following, wheel center positioning and bunker controls.

The new Danfoss Load Sensing valve block offers the latest in hydraulic technology to save fuel and tractor requirements.

An integrated oil tank and pump provides the drive of the flight conveyor, haulm web, cleaning webs



and rotor deflectors, while the tractor's own pump provides the drive of all cylinder functions and the picking web.

Flotation tyres, up to 600/55 – 26.5" are available for digging in difficult conditions.



### Technical Specifications 5660:

Total length :	8,80 m.
Transport height :	2,95 m.
Width :	2,99 m.
Net weight :	6100 kgs
Load on drawbar :	900 kgs
Hopper capacity:	6000 kgs



For more information and price quotations please contact:



Torlandsveien 3, N-4365 Nærbø, Norway  
Tel. +47 51 43 63 00, Fax +47 51 43 48 62  
www.tksmek.com e-mail: post@tksmek.no

Importer:

Dealer: