

# Underhaug UP3740 series

## 4-row potato planters – fast, accurate and reliable



Underhaug UP3740 are the latest 4-row potato planters in the UP3700 range. The design is based on experience from decades manufacturing some of the most sold potato planters in the world. The main focus has been on accuracy, technical features, ease of operation and durability, and the UP3700 series represents all of these.

Adjustable between 75 – 90 cms row widths, the UP3740 offers a choice of a fully hydraulic or mechanical drive, roller discs or ridge former to cover the seed, various types of opening shares, and high planting speed. This combined with a large hopper, 4 large land wheels, good visibility from the tractor cab, easy adjustments of all functions, makes UP3740 an obvious choice for today's potato growers.

The hydraulic/electronic version offers full hydraulic drive, infinite seed spacings set from the cab, automatic depth control and hopper tilting as options, planting monitor, speed control, seed control, area metering, field records, etc.

A traditional gear box drives the mechanical model, offers 30 seed spacings easily set by changing gears, and is otherwise as strong and well built as the hydraulic version.

The UP3700 is equipped with new steel cups, two different insert sizes in plastic, larger diameter turning drum at the top and adjustable mechanical belt agitation.

Technical specifications UP3740		
Models:	UP3741H	UP3742M
Number of rows:		4
Row distance:	75-90 cms	
Bunker Capacity:	2000kgs	
Wheel dimensions:	7.50 x 16"	
Marker arms, hydr.	standard	
Drive system:	hydr/el	mech
Tramlining kit	option	
Seed dist. mech. drive 30 steps:		10-60cms
Seed dist. hydr. drive stepless:	10-80 cms	
Planting monitor:	standard	option
Area meter:	standard	option
El. Adjust choke plates:	option	
Hydr. depth control:	standard	option
Aut. depth control:	option	na
Aut. bunker lifting:	option	na
Opening shares:	fixed / floating / HD w/shock absorbers	
Covering system:	roller discs - ridge former	
Weight:	1500kgs	
Mech belt agitation:	standard	
Hydr. belt agitation:	option	
El. belt agitation:	option	option
Insert cups	2 sizes	
<b>Chemical applications:</b>		
Granular applicator:	option	
Spraying equipment:	option	
<b>Dimensions:</b>		
Length:	2,90m	
Width:	3,45m	
Height:	2,57/1,65	
Filling height:	0,85m	



Manufacturer:

Dealer:



Torlandsveien 3, N-4365 Nærbø, Norway  
 Tel. +47 51 43 63 00, Fax +47 51 43 48 62  
 www.tks-as.no e-mail: post@tksmek.no

# **UNDERHAUG**

*4-row potato planters,  
the modern choice for efficient  
growers*

# **tkS**

**MEKANISKE**

[www.tksmek.com](http://www.tksmek.com)

